

KHE 56 (600340000) Combination Hammer (220-240 V / 50 - 60 Hz); Plastic Carry Case

Order no. 600340000 EAN 4007430167095



Product may differ from Image









- Combination hammer with 2 functions: hammer drilling and chiselling
- Metabo VibraTech (MVT): integrated damping system to reduce vibrations in order to protect the user's health
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised speeds, which remain constant under load
- Optional 30% impact reduction setting for working with more pliant materials
- Electronic soft start for precise spot-drilling
- Optimum heat dissipation and low weight thanks to die cast magnesium gear housing
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Service display, e.g. to indicate when the carbon brush needs to be replaced, and an LED indicating mains voltage
- Lockable switch for comfortable working in continuous operation

www.metabo.com 1/2



Technical data	
Characteristics	
Max. single blow energy (EPTA)	8.5 J
Maximum impact rate	2840 bpm
Rated input power	1300 W
Drill-Ø concrete with hammer drills	45 mm / 1 3/4 "
No-load speed	0 - 300 rpm
Bit retainer	SDS-max
Collar diameter	66 mm / 2 19/32 "
Weight (without power cable)	6.7 kg / 14.8 lbs
Cable length	6 m / 20 ft
Vibration	
Hammer drilling concrete	11.5 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Chiseling	9.7 m/s²
Uncertainty of measurement K	2.4 m/s²
Noise emission	
Sound pressure level	96 dB(A)
Sound power level (LwA)	107 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Metabo VibraTech (MVT) side handle

Duster

Plastic carry case

Drilling depth guide

Lubricant for tool shank end

www.metabo.com 2/2